

Q-SKJ1-24-CR

# Skaja 1

The following standards were taken into account:  
EN 15918:2011+A2:2017 + EN 1888-1:2018+A1:2022



Permissible total weight (Qeridoo + child + luggage)	50 kg
Maximum load (child + luggage)	35 kg
Tare weight trailer mode	15 kg
Maximum load in the trunk (luggage)	5 kg
Maximum load in the footwell (luggage)	1 kg
Maximum weight inner small pockets	0.5 kg
Maximum weight of child	22 kg
Minimum age with accessoires	1 month
Minimum age without accessoires	6 months
Age	4 years
Maximum body height	105 cm

Serial number &  
year of  
manufacture



## Qeridoo

Industriepark Nord 100  
53567 Buchholz  
Germany  
[www.qeridoo.de](http://www.qeridoo.de)  
[info@qeridoo.de](mailto:info@qeridoo.de)  
+49 (0) 2683 9466577  
Made in China





## WARNING!

EN

**The operation is only permitted under the following conditions. Non-compliance with these instructions can lead to serious injuries or fatal accidents!**

- » The user is at least 16 years old. He has read and understood the associated operating instructions.
- » Only 1 child can be transported. The child is secured using the harness system and wears suitable clothing and a bicycle helmet. A balanced load distribution must be ensured.
- » This seat unit is not suitable for children under 6 months. Unless you use compatible accessories. If the child can not sit independently, special accessories are mandatory (baby shell / hammock). Use a harness as soon as the child can sit unaided. Always use the restraint system. Never leave the child unattended.
- » This product is not suitable for running or skating. Running is only possible with optional accessories. The accessory is a product developed by the manufacturer and the jogger mode is not included in the scope of pushchairs and prams certification.
- » When driving, the insect net must be closed, the hand strap attached and the pennant inserted. Make sure the cabin is well ventilated when the temperature is high.
- » All safety requirements and regionally applicable legal requirements are fulfilled (e. g. lighting).
- » The Qeridoo should be fully assembled and in a technically faultless condition. All locks, straps and closures must be fastened. All screw connections should be tightened strongly.
- » The wheels have to lock in place and the brakes have to function properly.
- » Air pressure: Wheels 2.5 – 3 bar; buggy wheel max. 1.9 bar; jogger wheel 2.5 bar.
- » Any subsequent attachments or changes, in particular to the trailer coupling, can lead to accidents and defects.

**In trailer mode additionally applies:**

- » Permissible tow bar load at the trailer coupling: 0 – 8 kg
- » The tow bar must be connected to the bicycle frame via the coupler and the retaining strap. The buggy wheel must be removed.
- » The user is aware of the changed driving and braking behavior and drives defensively and with foresight.
- » The coupled trailer has a negative influence on the braking distance of the bicycle.
- » Maximum speed 20 km/h; in curves 7 km/h (walking pace).

**According to the German Road Traffic Licensing Act (StVZO), the following also applies:**

- » Maximum total weight for unbraked trailers: 40 kg